



## DISPERSANT 1252

### ORGANIC PENETRANT AND DISPERSANT

Description	<p><b>Dispersant 1252</b> has been specifically designed as a dispersant for microbiologically related fouling in a cooling tower system. It is best used on a regular basis to minimize the effects of biomass fouling of the system and the related corrosion mechanisms that might develop in the presence of a constant biofilm. Minimization of biofilm can lead to more effective inhibitor function, minimization of scale potential, and the inhibition of biofilm that can provide a protective cover for legionella bacteria.</p>
FDA Compliance	Not to be used in food contact.
Product Data	<p><b>pH:</b> 6  <b>SOLUBILITY:</b> Soluble  <b>APPEARANCE AND ODOR:</b> Clear, amber liquid, slight amine like odor.</p>
Dosage	<p><b>Dispersant 1252</b> should be added at a rate of 1 pint per 1000 gallons of system water (120 PPM) for a maintenance basis treatment, while doses of 300 to 1000 PPM may be needed for severely fouled systems.</p>
Safety & Handling	<p>Please refer to the MSDS before using or handling any product. In case of emergency contact Chem-Tel 24 hours a day at 1-800-255-3924.</p>
Storage	<p>Product should be protected from extremes in temperature. Store between 50-104 degrees F. Keep this and all chemicals away from flames and do not smoke or weld near container.  <b>PROTECT THIS PRODUCT FROM FREEZING</b></p>

400 Ternes Drive ■ Random Lake, WI 53075-1632 ■ Phone 920.994.2299

866.99.USE.CT ■ (866.998.7328) ■ Fax 920.994.4399 ■ [www.cleanerh2o.com](http://www.cleanerh2o.com)