



INHIBITOR 2200

CORROSION INHIBITOR FOR STEAM BOILERS

Description	Inhibitor 2200 was designed as a temporary corrosion inhibitor for steam boilers. The product contains necessary pH bolstering chemicals and oxygen scavenger to minimize corrosion until the regular water treatment program has been started.
FDA Compliance	Not to be used in food contact.
Product Data	APPEARANCE AND ODOR: Brown powder.
Dosage	The recommended dose is one pound per thousand gallons if the boiler is expected to be stored for more than a few days. In larger concentrations the product can be used to remove incidental oil from tube installation. If it is believed that there is an excess amount of oil, contact your Chem-Tech representative for a dosage. The minimum amount recommended for this purpose is 60 lbs. per thousand gallons.
Safety & Handling	Please refer to the MSDS before using or handling any product. In case of emergency contact Chem-Tel 24 hours a day at 1-800-255-3924.
Storage	Product should be protected from extremes in temperature. Store between 50-104 degrees F. Keep this and all chemicals away from flames and do not smoke or weld near container. PROTECT THIS PRODUCT FROM FREEZING

400 Ternes Drive ■ Random Lake, WI 53075-1632 ■ Phone 920.994.2299

866.99.USE.CT ■ (866.998.7328) ■ Fax 920.994.4399 ■ www.cleanerh2o.com